

Safety Data Sheet

This safety data sheet was created pursuant to the requirements of: Regulation(EC)
No. 1907/2006 and Regulation (EC) No.1272/2008

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name Bridgebond™ 5 Litre Part A
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives.
Uses advised against Consumer use

1.3. Details of the supplier of the safety data sheet

Company Name

Bridge Rubber & Plastics Ltd
Smith's Quay, Hazel Road
Woolston
Southampton, SO19 7GB
UK Tel: +44 (0)23 80434646
Fax: +44 (0)23 80437978

E-mail address info@bridgerubber.co.uk

1.4. Emergency telephone number

United Kingdom +44 (0)2380 434646 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation

Serious eye damage/eye irritation

Reproductive toxicity	Category 2 - (H315)
Specific target organ toxicity (single exposure)	Category 2 - (H319)
Specific target organ toxicity (repeated exposure)	Category 2 - (H361)
Chronic aquatic toxicity	Category 3 - (H336)
Flammable liquids	Category 2 - (H373)
	Category 2 - (H411)
2.2. Label Elements	Category 2 - (H225)

Contains: Toluene, Methyl ethyl ketone, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6, isoalkanes, <5% n-hexane



Signal word
DANGER

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

Hazard statements

H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361d - Suspected of damaging the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects
H225 - Highly flammable liquid and vapour

EU Specific Hazard Statements

EUH208 - Contains rosin. May produce an allergic reaction

Precautionary statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260 - Do not breathe mist/vapours/spray
P273 - Avoid release to the environment
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P391 - Collect spillage
P403 + P235 - Store in a well-ventilated place. Keep cool
P235 - Keep cool
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public.
Reserved for industrial and professional use.

2.3. Other Hazards

In use may form flammable/explosive vapour-air mixture

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical Name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Toluene	203-625-9	108-88-3	>25 - <40	Skin Irrit. 2 (H315) Repr. 2 (H361d) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Flam. Liq. 2 (H225)		01-2119471310-51-XXXX
Methyl ethyl ketone	201-159-0	78-93-3	>25 - <40	Eye Irrit. 2		01-2119457290-

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

				(H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)		43-XXXX
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	--	10 - <20	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)		01-2119475515- 33-xxxx
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	--	5 - <10	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066) Skin Sens. 1		01-2119484651- 34-XXXX
Rosin	232-475-7	8050-09-7	0.1 - <1	(H317)		01-2119480418- 32-XXXX
Zinc oxide	215-222-5	1314-13-2	0.1 - <1	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)		01-2119463881- 32-XXXX
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene	271-867-2	68610-51-5	0.1 - <1	Aquatic Chronic 4 (H413) Repr. 2 (H361d)		01-2119496062- 39-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean mouth with water and drink afterwards plenty of water. Call a doctor or poison control centre immediately.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams. CAUTION: Use of water spray when fighting fire may be inefficient.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous Combustion Products	Carbon oxides.

5.3. Advice for firefighters

Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Avoid contact with skin, eyes or clothing. Avoid breathing vapours or mists. Ensure adequate ventilation. Use personal protective equipment as required. See section 8 for more information. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow to enter into soil/subsoil.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

Methods for containment	Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.
Prevention of secondary hazards	Eliminate all ignition sources if safe to do so.
6.4. Reference to other sections	
Reference to other sections	See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in an area equipped with sprinklers. Avoid contact with skin, eyes or clothing. Avoid breathing vapours or mists. Use personal protection equipment. See section 8 for more information.
General hygiene considerations	Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended. Take off all contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store locked up.
---------------------------	---

7.3. Specific end use(s)

Specific Use(s)

Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information	Observe technical data sheet.
--------------------------	-------------------------------

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits

Chemical Name	European Union	Ireland	United Kingdom
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m ³ *	TWA: 192 mg/m ³ TWA: 50 ppm STEL: 384 mg/m ³ STEL: 100 ppm Sk*	TWA: 50 ppm TWA: 191 mg/m ³ STEL: 100 ppm STEL: 384 mg/m ³ Sk*
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ Sk*	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 899 mg/m ³ Sk*
Magnesium oxide (MgO) 1309-48-4		TWA: 4 mg/m ³ TWA: 5 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

		TWA: 10 mg/m ³ STEL: 10 mg/m ³ STEL: 12 mg/m ³ STEL: 30 mg/m ³	STEL: 30 mg/m ³ STEL: 12 mg/m ³
Rosin 8050-09-7	-	TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³	TWA: 0.05 mg/m ³
Zinc oxide 1314-13-2	-	TWA: 2 mg/m ³ STEL: 10 mg/m ³	-
Chemical Name		Ireland	
Methyl ethyl ketone 78-93-3	European Union	-	United Kingdom
	-		70 µmol/L urine

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)
Toluene (108-88-3)

Type Long term Systemic health effects Worker
 Exposure route Dermal
 Derived No Effect Level (DNEL) 384 mg/kg bw/d

Type Long term Systemic health effects Local health effects Worker
 Exposure route Inhalation
 Derived No Effect Level (DNEL) 192 mg/m³

Type Short term Local health effects Systemic health effects Worker
 Exposure route Inhalation
 Derived No Effect Level (DNEL) 384 mg/m³

Methyl ethyl ketone (78-93-3)

Type Worker Long term Systemic health effects
 Exposure route Dermal
 Derived No Effect Level (DNEL) 1161 mg/kg bw/d

Type Worker Long term Systemic health effects
 Exposure route Inhalation
 Derived No Effect Level (DNEL) 600 mg/m³

Zinc oxide (1314-13-2)

Type Worker Long term Systemic health effects
 Exposure route Inhalation
 Derived No Effect Level (DNEL) 5 mg/m³

Type Worker Long term Local health effects
 Exposure route Inhalation
 Derived No Effect Level (DNEL) 0.5 mg/m³

Type Worker Long term Systemic health effects
 Exposure route Dermal
 Derived No Effect Level (DNEL) 83 mg/kg bw/d

Derived No Effect Level (DNEL)

Methyl ethyl ketone (78-93-3)

Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	412 mg/kg bw/d

Type	Consumer Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	106 mg/m ³

Type	Consumer Local health effects Systemic health effects
------	---

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

Exposure route	Oral
Derived No Effect Level (DNEL)	31 mg/kg bw/d
Zinc oxide (1314-13-2)	
Type	Consumer Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	2.5 mg/m ³
Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	83 mg/kg bw/d
Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	0.83 mg/kg bw/d

Predicted No Effect Concentration No information available.

(PNEC)

Predicted No Effect Concentration (PNEC)

Methyl ethyl ketone (78-93-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	55.8 mg/l 55.8 mg/l 287.74 mg/l 287.7 mg/l
Marine water	22.5 mg/l
Freshwater sediment	
Marine sediment	
Soil	

Zinc oxide (1314-13-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0206 mg/l 0.0061 mg/l 235.6 mg/kg dry
Marine water	weight 113 mg/kg dry weight 106.8 mg/kg
Freshwater sediment	dry weight 0.1 mg/l
Marine sediment	
Soil	
Microorganisms in sewage treatment	

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection
Hand protection
Skin and body protection
Respiratory protection
Recommended filter type:

Tight sealing safety goggles. Face protection shield. Eye protection must conform to standard EN 166.

Wear protective gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.

Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective clothing.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. In case of inadequate ventilation wear respiratory protection. Organic gases and vapours filter conforming to EN 14387.

Do not allow into any sewer, on the ground or into any body of water.

Environmental exposure controls

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State	Liquid
Appearance	Liquid
Colour	Off-white

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

Odour	Characteristic		
Odour Threshold	No information available		
Property	Values	Remarks	Method
pH	No data available		
Melting point / freezing point	No data available		
Boiling point / boiling range	approx. 48 °C		
Flash Point	approx. -9 °C		
Evaporation Rate	No data available		
Flammability (solid, gas)	No data available		
Flammability Limit in Air			
Upper flammability or explosive limits	No data available		
Lower flammability or explosive limits	No data available		
Vapour Pressure	No data available		
Vapour Density	No data available		
Relative Density	0.9		
Water Solubility	Immiscible in water		
Solubility(ies)	No data available		
Partition coefficient	No data available		
Autoignition Temperature	No data available		
Decomposition Temperature	No data available		
Kinematic Viscosity	approx. 50 mm ² /s		
Dynamic Viscosity	approx. 2500 mPa s	@ 40°C	
Explosive properties	No data available		
Oxidising properties	No data available		
9.2. Other information			
Solid content (%)			
Softening Point	approx. 22		
Molecular Weight	No information available		
VOC (volatile organic compound)	No information available		
Density	No information available		
Bulk Density	No information available		

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical impact No.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product information

Inhalation May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Irritating to eyes. Causes serious eye irritation.

Skin contact Causes skin irritation.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity

Acute Toxicity

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Toluene 108-88-3	= 5580 mg/kg (Rat) = 2483 mg/kg (Rat) LD50 >5840 mg/kg Rat	= 12000 mg/kg (Rabbit) = 5000 mg/kg (Rabbit) LD50 >2920 mg/kg (Rat)	= > 20 mg/L (Rat) 4 h = 17700 ppm (Rat) 4 h
Methyl ethyl ketone 78-93-3			
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics --			
Hydrocarbons, C6, isoalkanes, <5% n-hexane -- Rosin	>16750 mg/Kg (rat)	>3350 mg/Kg (rabbit OECD 402)	259354 mg/m ³ (vapour) (rat OECD 403)
8050-09-7 Zinc oxide	>2800 mg/Kg (rat)	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h
1314-13-2 Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	> 5000 mg/kg (Rat) > 5000 mg/kg (Rat)	LD50 >2000 mg/Kg (Rat) (OECD 402) > 5010 mg/kg (Rabbit)	LC50 (4h) >5.7 mg/l > 165 mg/L (Rat) 1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

Skin corrosion/irritation	Classification based on data available for ingredients. Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Classification based on data available for ingredients. Contains a known or suspected reproductive toxin. The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical Name	European Union
Toluene 108-88-3	Repr. 2

Component Information		
Toluene (108-88-3)		
Method	Species	Results
OECD 407	in vivo	reproductive toxicant

STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static) LC50: 3130	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)	-
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)	-
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics --		-	-	EL50 (48h) = 3mg/L Daphnia	-

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

Hydrocarbons, C6, isoalkanes, <5% n-hexane --	13.6 mg/l (Pseudokirchneriella subcapitata)	18.3 mg/l (Oncorhynchus mykiss)	-	31.9 mg/l (Daphnia magna)	-
Rosin 8050-09-7	EC50: =400mg/L (72h, Desmodesmus subspicatus)	LC50 (96h) >10mg/L Fish (Danio rerio)	EC50 = 31.5 mg/L 30 min	EC50 48 h >100 mg/L (Daphnia magna)	-
Zinc oxide 1314-13-2	LC 50 (72Hr) 0.136 mg/L EC50: >0.2mg/L (72h,	LC50 (96h) =0.7 mg/L Fish (Danio rerio)	-	LC 50 (48Hr) =0.5 mg/l (Ceriodaphnia dubia)	-
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	Pseudokirchneriella subcapitata)	LC50: >0.2mg/L (96h, Oncorhynchus mykiss)	-	EC50: >0.2mg/L (48h, Daphnia magna)	-

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information

Methyl ethyl ketone (78-93-3)

Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

Zinc oxide (1314-13-2)

Method	Exposure time	Value	Results
			The methods for determining biodegradability are not applicable to inorganic substances

12.3. Bioaccumulative potential

Bioaccumulative potential There is no data for this product.

Component Information

Chemical Name	Partition coefficient	Bioconcentration factor (BCF)
Toluene 108-88-3	2.7 0.3 3.6	-
Methyl ethyl ketone 78-93-3		501
Hydrocarbons, C6, isoalkanes, <5% n-hexane --		
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	7.93	-

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical Name	PBT and vPvB assessment
Toluene 108-88-3	The substance is not PBT / vPvB PBT assessment does not apply
Methyl ethyl ketone 78-93-3	The substance is not PBT / vPvB The substance is not PBT / vPvB
Rosin 8050-09-7	Further information relevant for the PBT assessment is necessary The substance is not PBT / vPvB
Zinc oxide 1314-13-2	PBT assessment does not apply The substance is not PBT / vPvB
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene 68610-51-5	

12.6. Other adverse effects

Other Adverse Effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN Number UN1133

14.2 Proper Shipping Name Adhesives, Environmentally Hazardous

14.3 Transport hazard class(es) 3

Labels 3

14.4 Packing Group II

Description UN1133, Adhesives, 3, II, (D/E), Environmentally Hazardous

14.5 Environmental hazards Yes

14.6 Special Provisions 640D

Classification Code F1

Tunnel restriction code (D/E)

Limited Quantity (LQ) 5 L

ADR Hazard Id (Kemmler Number) 33

IMDG

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

14.1 UN Number	UN1133
14.2 Proper Shipping Name	Adhesives (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Zinc oxide), Marine Pollutant
14.3 Transport hazard class(es)	3
14.4 Packing Group	II
Description	UN1133, Adhesives (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Zinc oxide), 3, II, (-9°C c.c.), Marine Pollutant
14.5 Marine Pollutant	P
14.6 Special Provisions	None
Limited Quantity (LQ)	5 L
EmS-No.	F-E, S-D
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available

Air transport (ICAO-TI / IATA-DGR)

14.1 UN Number	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing Group	II
Description	UN1133, Adhesives, 3, II
14.5 Environmental hazards	Yes
14.6 Special Provisions	A3
Limited Quantity (LQ)	1 L
ERG Code	3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical Name	CAS No.	Restricted substance per REACH Annex XVII
Toluene	108-88-3	48.

48 . Reserved for industrial and professional use. Adhesives or spray paint shall not be placed on the market containing above substance equal to or greater than 0.1% where supplied to the general public.

EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS
P5b - FLAMMABLE LIQUIDS
P5c - FLAMMABLE LIQUIDS
E2 - Hazardous to the Aquatic
Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National Regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No

Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation
H361d - Suspected of damaging the unborn child
H336 - May cause drowsiness or dizziness
H373 - May cause damage to organs through prolonged or repeated exposure
H304 - May be fatal if swallowed and enters airways
H225 - Highly flammable liquid and vapour
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H413 - May cause long lasting harmful effects to aquatic life
H319 - Causes serious eye irritation
H317 - May cause an allergic skin reaction
H411 - Toxic to aquatic life with long lasting effects
EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals		
STOT RE	Specific target organ toxicity - Repeated exposure		
STOT SE	Specific target organ toxicity - Single exposure		
EWC:	European Waste Catalogue		

Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

Prepared By Product Safety & Regulatory Affairs

Revision Date 08-Jan-2019

Indication of changes

Revision note Not applicable.

United Kingdom, Ireland - BE

Safety Data Sheet

Bridgebond™ 5 Litre Part A
Supersedes Date: 08/01/2019

Revision Date 23/03/2026
Revision Number 1.01

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet